



SOLAR HOT WATER

STAINLESS STEEL SPLITSOLAR HOT WATER SYSTEMS

Split Solar Hot Water Systems have the storage tank mounted on the ground in a convenient location. Solar energy is collected by the roof mounted solar collectors. Heated water is transferred from the solar collectors to the tank by an innovative control system that operates when solar energy is available.

BENEFITS OF SOLAR HOT WATER

Australian electricity is predominantly generated using non renewable and dirty coal fired power stations. As well as electricity they produce carbon dioxide emissions, ash, particles and waste heat, while consuming vast quantities of water and non renewable coal. Solar hot water systems reduce the need for electricity to be generated at all and are part of many major energy reduction programs. Installing a solar hot water system will reduce your electricity usage and your carbon foot print.

FEATURES OF EQUINOX STAINLESS STEEL SPLIT SYSTEM

- Reduction in energy costs to heat the water used in your home.
- Stainless steel hot water storage tank, a material you can trust for cleanliness and long life.
- Ground level tank minimises the impact on the aesthetics of your roof.
- High efficiency collectors to absorb the maximum available solar energy. (collectors also available for frost prone areas)
- Colourbond® outer skin to provide good asthetics.
- It is the ideal system for the construction of a new home or a major renovation.
- Equinox split system solar controllers incorporate a sophisticated IEC intelligent electronic controller. The IEC controller uses algorithms to switch the transfer pump to collect solar energy but not short cycle or cause the tank to overheat reducing the stress on the pump and tank and preventing safety valve from wasting hot water.
- · Designed by Rinnai, a household name in efficient water heating.
- Made in Australia at Rinnai's manufacturing plant with in-line gas boosters made by Rinnai Japan.




SYSTEM SELECTION

Solar hot water system sizing is based on the number of people in your household as well as the usage. When selecting a system consider whether you have average or high hot water use. If you have a spa bath and/or utilise a lot of hot water for washing, consider selecting a larger system, or adding a collector.

Model	Tank	Collectors	Booster	STC Enduro/FTC				STC E-Frost				System Selection	
				Z 1	Z2	Z 3	Z 4	Z 1	Z2	Z3	Z 4	Average Usage	High Usage
SB252ES	250	2	3.6 kW Electric	16	17	16	14	16	17	16	14	8 People	5 People
SM252ES	250	2	3.6 kW MID Electric	36	41	35	32	29	31	28	26	5 People	3 People
SB312ES	315	2	3.6 kW Electric	25	27	24	21	24	25	22	19	10 People	6 People
SM312ES	315	2	3.6 kW MID Electric	30	32	31	28	28	30	27	25	7 People	4 People
SB313ES	315	3	3.6 kW Electric	27	28	27	24	27	28	26	23	10 People	6 People
SM313ES	315	3	3.6 kW MID Electric	42	45	42	37	39	42	38	33	7 People	4 People
SP252GS	250	2	S20 Gas	37	41	37	32	27	30	28	24	8 People	5 People
SP252GS	250	2	S26 Gas	37	41	37	32	27	30	28	24	8 People	5 People
SP312GS	315	2	S26 Gas	36	41	36	32	26	29	27	24	10 People	6 People
SP313GS	315	3	S26 Gas	41	44	43	38	37	41	37	32	10 People	6 People

STCs & EQUINOX SOLAR SYSTEMS





COLLECTORS

All Equinox Stainless Steel Split Systems are available with Enduro, Excelsior and E-Frost Solar collectors. These are highly efficient flat plate solar collectors with copper tubes offering the largest possible solar collection area. Enduro and Excelsior collectors are also available in a Frost Tolerant (FTC) version. Select FTC as advised by your Equinox Solar Dealer.

Enduro Collectors offer a well insulated aluminium case, solar glass and aluminium finned risers incorporating a black selective surface to collect and retain as much solar energy as possible, resulting in industry benchmark efficiency.

Excelsior Collectors offer TiNOX, the latest 'blue absorber surface' European technology that delivers efficiency and a certified performance over its long life.

E-Frost Collectors combine the best features from Flat plate solar collectors and evacuated tube collectors resulting in high performance and high level frost protection. Choose E-Frost for heavy frost areas (-12°C).

BOOSTERS

Boosters bring the solar heated water to final temperature during times of low solar availability and/ or excessive hot water use. Equinox offer both electric and gas boosters to match your fuel choice.

Electric Boosters heat the volume of water in the tank above the electric element. There are three electric element positions available, each providing a balance between efficiency and on-demand capability.

Gas Boosters use the dedicated solar version of the market leading Rinnai INFINITY as an in-line gas booster. Only operating if and when required, in-line gas boosting will never run out.

WARRANTY

Tanks - 10 Years*, Collectors - 7 Years*.

For further information on warranty conditions and exclusions please contact your local Equinox Solar Dealer

WEBSITE

www.equinoxsolar.com.au

EQUINOX DEALER

 ${\bf Contact\ your\ Equinox\ Solar\ Dealer\ for\ further\ information.}$